



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G02C 7/04	A1	(11) International Publication Number: WO 00/48036 (43) International Publication Date: 17 August 2000 (17.08.00)
<p>(21) International Application Number: PCT/GB00/00445</p> <p>(22) International Filing Date: 11 February 2000 (11.02.00)</p> <p>(30) Priority Data: 9903170.0 13 February 1999 (13.02.99) GB</p> <p>(71) Applicant (for all designated States except US): CONTACT LENS PRECISION LABORATORIES LIMITED [GB/GB]; Mill Lane, Sawston, Cambridge CB2 4HZ (GB).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): CLAMP, John, Haldyn [GB/GB]; 89 Thoday Street, Cambridge CB1 3AT (GB).</p> <p>(74) Agent: MORTON, Colin, David; Keith W Nash & Co, 90-92 Regent Street, Cambridge CB2 1DP (GB).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: CONTACT LENSES AND METHODS OF MANUFACTURE</p> <div data-bbox="438 1092 1153 1659"> </div> <p>(57) Abstract</p> <p>The invention relates to a method of manufacturing a contact lens having an aspheric front surface computed by a method that allows total power control at each point of the lens by controlling power across the optic area of the lens, or each incremental part thereof. The lens can be monofocal, multifocal, toric, prismatic or a combination of these and be manufactured by any method such as lathe-cutting and cast-moulding. The lens can be manufactured to impart a chosen substantially uniform focal power over the optic area of the lens, or each incremental part thereof, either when in air or when part of the lens-eye system when in situ on the eye. The invention allows for the optimisation of the method of manufacturing the front surface of the lens, by fitting the most suitable mathematical equations dependent on the accuracy of the manufacturing equipment.</p>		